

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A blood purification device comprising:

a blood circuit having an arterial blood circuit and a venous blood circuit;

a blood pump disposed in said arterial blood circuit;

a blood purifier connected to the blood circuit between said arterial blood circuit and said venous blood circuit, and configured to purify blood flowing in said blood circuit;

a first measuring unit disposed in said arterial blood circuit and configured to measure a blood concentration of said arterial blood circuit;

a second measuring unit disposed in said venous blood circuit and configured to measure a blood concentration of said venous blood circuit;

a calculating unit configured to calculate a first measurement value and a first theoretical value, ~~[[the]]~~ said first measurement value referring to a ratio of said blood concentrations measured by said first measuring unit and said second measuring unit, and ~~[[the]]~~ said first theoretical value referring to a blood concentration ratio obtained by at least one formula based on parameters including a preset blood flow rate of said blood pump and a preset blood purifying rate of said blood purifier; and

an evaluation unit configured to evaluate whether a difference between said first measurement value and said first theoretical value ~~are approximately equal~~ is larger than a predetermined acceptable ratio difference; and

4. - 7. (Canceled)

8. (New) The blood purification device of claim 1, wherein:

said blood pump is further configured to adjust the preset blood flow rate to an adjusted blood flow rate;

said calculation unit is further configured to calculate a second measurement value and a second theoretical value, the measurement value referring to a ratio of said blood concentrations measured by said first measuring unit and said second measuring unit while said blood pump is operated at said adjusted blood flow rate and said blood purifier is operated at said preset blood purifying rate, and the theoretical value referring to a blood concentration ratio obtained by at least one formula based on parameters including said adjusted blood flow rate of said blood pump and said preset blood purifying rate of said blood purifier;

said evaluation unit is further configured to evaluate whether said difference between said first measurement value and said first theoretical value is approximately equal to a difference between said second measurement value and said second theoretical value; and

said reporting unit is further configured to report the trouble condition for said blood purifier when said difference between said first measurement value and said first theoretical value is approximately equal to said difference between said second measurement value and said second theoretical value, and to report the trouble condition for said blood pump when said difference between said first measurement value and said first theoretical value is not approximately equal to said difference between said second measurement value and said second theoretical value.

9. (New) A method for monitoring for a trouble condition associated a blood purification device, the method comprising the steps of:

disposing a blood pump in an arterial blood circuit of said blood purification device;

connecting a blood purifier between said arterial blood circuit and a venous blood circuit of the blood purification device, said blood purifier being configured to purify blood flowing in said blood circuit;

measuring a blood concentration of said arterial blood circuit;

measuring a blood concentration of said venous blood circuit;

calculating a measurement value and a theoretical value, the measurement value referring to a ratio of said blood concentrations of said arterial blood circuit and said venous blood circuit, and the theoretical value referring to a blood concentration ratio obtained by at least one formula based on parameters including a preset blood flow rate of said blood pump and a preset blood purifying rate of said blood purifier;

evaluating whether a difference between said measurement value and said theoretical value is larger than a predetermined acceptable ratio difference; and

reporting the difference between said measurement value and said theoretical value when that difference is larger than the predetermined acceptable ratio difference, wherein said reporting unit indicates a trouble condition for at least one of said blood pump and said blood purifier.